

Inch Tapered Roller Bearing

| Номер подшипника. | Граничные размеры (мм) | | | | | | | Базовая грузоподъемность (кН) | |
|-------------------|------------------------|----------|---------|------|-------|------|------|-------------------------------|-------------------|
| | д: | Б: | R | Д: | С | г | Т | Динамический (Cr) | Статический (Cor) |
| M249747/710 | 257,175 | 358,775 | 71,438 | 842 | 1760 | 156 | 1200 | 1700 | 20,5 |
| 38880/38820 | 263,525 | 325,438 | 28,575 | 220 | 550 | 48 | 1300 | 1800 | 53,0 |
| L555249/210 | 292,100 | 374,650 | 47,625 | 501 | 1140 | 98 | 1100 | 1600 | 12,0 |
| L555249/210/VE174 | 292,100 | 374,650 | 47,625 | 501 | 1140 | 98 | 1100 | 1600 | 12,0 |
| L357049/010/VE174 | 304,800 | 393,700 | 50,800 | 528 | 1220 | 104 | 1000 | 1500 | 14,5 |
| LM361649A/610 | 343,154 | 450,850 | 66,675 | 935 | 2200 | 180 | 900 | 1300 | 28,0 |
| L865547/512 | 381,000 | 479,425 | 49,250 | 594 | 1500 | 120 | 800 | 1200 | 20,0 |
| HM266449/410 | 384,175 | 546,100 | 104,775 | 1870 | 4150 | 320 | 750 | 1100 | 77,0 |
| LL566848/810/HA1 | 403,225 | 460,375 | 28,575 | 246 | 765 | 58,5 | 800 | 1200 | 6,70 |
| LM567949/910/HA1 | 406,400 | 549,275 | 85,725 | 1380 | 3050 | 236 | 700 | 1000 | 53,5 |
| LM770949/910 | 457,200 | 603,250 | 85,725 | 1450 | 3400 | 265 | 630 | 950 | 61,5 |
| LM772748/710/HA1 | 488,950 | 634,873 | 84,183 | 1450 | 3650 | 265 | 600 | 850 | 63,5 |
| EE243196/250/HA2 | 498,475 | 634,873 | 80,962 | 1470 | 3650 | 270 | 600 | 850 | 59,5 |
| EE843220/290 | 558,800 | 736,600 | 88,108 | 1830 | 4150 | 305 | 500 | 750 | 92,5 |
| LM377449/410 | 558,800 | 736,600 | 104,775 | 2330 | 5700 | 405 | 500 | 750 | 115 |
| EE649240/310 | 609,600 | 787,400 | 93,662 | 2160 | 5300 | 380 | 450 | 670 | 110 |
| EE649240AX/310 | 609,600 | 787,400 | 93,662 | 2160 | 5300 | 380 | 450 | 670 | 110 |
| LM283649/610/HA1 | 749,300 | 990,600 | 159,500 | 4570 | 12000 | 750 | 340 | 500 | 330 |
| L183448/410 | 760,000 | 889,000 | 88,900 | 1870 | 5850 | 380 | 360 | 530 | 94,0 |
| LL483449/418 | 762,000 | 889,000 | 69,850 | 1230 | 3800 | 255 | 380 | 560 | 66,5 |
| L183449/410 | 762,000 | 889,000 | 88,900 | 1870 | 5850 | 380 | 360 | 530 | 94,0 |
| EE763330/410 | 838,200 | 1041,400 | 93,662 | 1900 | 4800 | 320 | 320 | 460 | 160 |